PRODUCT DATASHEET

1843SF PALAIS ROYAL

LED spotlight surface-mounted on roadways for raking or extensive illumination.

APPLICATIONS:

- Cycle paths and pedestrian paths lighting
- Roadway lighting
- Public space lighting
- Low facades lighting
- Footbridges and piers

CARACTERISTICS 1 beam direction

- Colourless anodised machined aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws Mounted directly on roadway
- or to recess plateWithstands occasional traffic
- from all kinds of vehicles



162

山

98

 \bigcirc

192 135

LEC



APPLICATION Outdoor lighting Standard flux : 210 lm This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K) CONFIGURATEUR.EMPLACEMENT Ground recessed fittings Pavements sides CARACTERISTICS Weight : 715 g **Options of luminous effects** 🗙 Non adjustable Paralell beam Beam with various openings Transparent flat window **Power supply - Control** Cable length: 1 m Integrated : 24V-PWM Remote : 24V-0/10V, 24V-DMX, 24V-DALI Integrated: 230V-Non dimmable Material Anodised glazed aluminium (AL)Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2 **Mechanical strength - Waterproofness** Protrusion which is an obstacle for 2-wheels vehicles and pedestrians. The unit should be (the set permanently lit to draw attention to the obstacle. Withstands random all vehicles traffic Withstands low-speed light vehicles traffic Certified in compliance with European Standards 60598-2-22 for emergency E lighting units Resists compression up to 8 **8T** tons IK10 Resists impacts up to IK10 40J 40J Tight for extended IP68 immersion

 Number of LEDs
 2

 Type of LEDs
 Power LEDs. Contact us for hot countries.

 Color(s)
 Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O),

Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link: http://www.lec-lyon.com/1843sf-palais-royal-r1311

http://www.iee iyon.com/ 10403i palais royar i

O

PDF generated on 19.05.2024

www.lec-lyon.com


Technical data is subject to changes. Luminaire guaranteed 5 years. Luminaire designed and manufactured in France.

OPTIC DATASHEET



1843SF PALAIS ROYAL

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/1843sf-palais-royal-r1311



PDF generated on 19.05.2024

www.lec-lyon.com

Technical data is subject to changes. Luminaire guaranteed 5 years. Luminaire designed and manufactured in France.