# **PRODUCT DATASHEET**



## 5727 **ALICANTE**

«Maxi» version in the orientable recessed round lights range.

Spotlight swivels 360° in its recess to direct the beam in the right direction with no installation constraints.

Independently adjustable tiltable parallel plates (-3° to +26°) by external adjustment without opening the fitting or compromising its water resistant.


#### **APPLICATIONS:**

- Medium height facade lighting
- (10m) • Highlight architectural features, street furniture,
- trees... • Squares and public spaces

#### CARACTERISTICS

- Colourless anodised aluminium body and collar
- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed
- 2 possible recess dimensions
- Withstands occasional traffic from all kinds of vehicles
- RGBW Option available







Number of LEDs	18
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5727-alicante-r393

## APPLICATION

### Outdoor lighting Standard flux : 4014 lm This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K) CONFIGURATEUR.EMPLACEMENT Ground flush recessed fittings Ground recessed fittings CARACTERISTICS Weight : 4600 g eco design Eco Design **Options of luminous effects** RGBW option Adjustable on 2 axis (2) Rotating beam Beam with various openings Transparent flat window Colour control system (optional) **Power supply - Control** ᠵ Cable length: **1 m** Integrated: 24V-Non dimmable Integrated : 230V-Non dimmable, 230V-0/10V, 230V-DMX, 230V-DALI Material (AL) Anodised glazed aluminium 316L Stainless steel (316L) Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2 **Mechanical strength - Waterproofness** Withstands random all vehicles traffic IK10 Resists impacts up to IK10

60J 60J Tight for extended IP68 immersion

Adjustable orientation JP) without dismantling

PDF generated on 19.05.2024


www.lec-lyon.com


Technical data is subject to changes. Luminaire guaranteed 5 years. Luminaire designed and manufactured in France.





### **5727 ALICANTE**


This datasheet gives you all the available optics for this product, consistent with the number of LEDs. **URL of this product:** http://www.lec-lyon.com/5727-alicante-r393





















130x25° (L1)










130x25°D50° (L5)



PDF generated on 19.05.2024

www.lec-lyon.com

Technical data is subject to changes. Luminaire guaranteed 5 years. Luminaire designed and manufactured in France.