

1750H **BOURGOGNE**

«Mini» version in the round flush recessed raking light range. Choice of lighting effects for customised marker-lighting. RGB options available.

APPLICATIONS:


- · Decorative or safety markerlighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

CARACTERISTICS

Uniform window Colourless anodised machined aluminium body

- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1750K and 1750DS)
- 3 possible recess dimensions
- · Withstands occasional traffic from all kinds of vehicles (1750 & 1750H)





Number of LEDs	3
Type of LEDs	120° SMD LEDs (S), SMD trichro (A)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), RVB (T)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1750hz-bourgogne-r969

APPLICATION

Marker-lighting

CONFIGURATEUR.EMPLACEMENT

Ground flush recessed fittings

Ground recessed fittings

Pavements sides

CARACTERISTICS

Weight: 120 g

Options of luminous effects



RGB options



Non adjustable



Flat homogeneous window



Colour control system (optional)

Power supply - Control

Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Material



(AL) Anodised glazed aluminium



Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness



Withstands random all vehicles traffic

IK10 Resists impacts up to IK10 60J 60J

IP68 Ingrition c. immersion Tight for extended