

## 5716 ALLEVARD

«Medium» version in the orientable recessed round lights range.

Spotlight swivels 360° in its recess to direct the beam in the right direction with no installation constraints.

LED plate is tiltable (+/-25°) by external adjustment without opening the fitting or compromising its water resistant.

### APPLICATIONS:

- Low facade lighting (5m)
- Highlight architectural features, street furniture, small trees...

### CARACTERISTICS

- Anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed
- 2 possible recess dimensions
- Withstands occasional traffic from all kinds of vehicles
- RGBW options available



Number of LEDs	6, 7
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:  
<http://www.lec-lyon.com/5716-allevard-r97>



### APPLICATION

#### Outdoor lighting

Standard flux : **1561 lm**

*This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)*






### CONFIGURATEUR.EMPLACEMENT

-  Ground flush recessed fittings
-  Ground recessed fittings





### CARACTERISTICS

Weight : **2300 g**




### Options of luminous effects

-  RGBW option
-  Adjustable on 2 axis
-  Rotating beam
-  Beam with various openings
-  Transparent flat window
-  Colour control system (optional)





### Power supply - Control

-  Cable length: **1 m**
-  **Integrated** : 24V-Non dimmable, 24V-PWM, 24V-DMX
-  **Remote** : 24V-0/10V, 24V-DALI
-  **Integrated** : 230V-Non dimmable, 230V-PWM, 230V-0/10V, 230V-DMX, 230V-DALI

### Material

-  Anodised glazed aluminium
-  316L Stainless steel
-  Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

### Mechanical strength - Waterproofness

-  Withstands random all vehicles traffic
-  **IK10 60J** Resists impacts up to IK10 60J
-  **IP68** Tight for extended immersion
-  Adjustable orientation without dismantling

## 5716 ALLEVARD

This datasheet gives you all the available optics for this product, consistent with the number of LEDs.

URL of this product: <http://www.lec-lyon.com/5716-allevard-r97>

